

# INTERACTIVE UPS GS2000



## Product Feature

- Specially designed for personal computer with multi functions
- Microprocessor control guarantees high reliability
- Equipped with Boost and Buck AVR
- Green Power Function for energy saving
- DC Start Function
- Auto restart while AC recovery
- Compact size, Light Weight
- Provides AC Overload protection

## Product Form Type

Product Form Type	GS2000
Capacity	2000 VA / 1200 W
<b>INPUT</b>	
Voltage	220Vac / 230 Vac
Voltage Range	140-290Vac / 140 - 300 Vac
Frequency Range	>40Hz (autosensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt.mode)	220Vac / 230Vac±10%
Frequency Range (Batt. Mode)	50Hz±1Hz or 60Hz±1Hz
Transfer Time	Typical 4-8ms, 13 ms max
Waveform (Batt.mode)	Simulated Sine Wave
<b>EFFICIENCY</b>	
Battery Voltage	24V
Battery Number	9AH*2
Charge Current	1.0 A
<b>INDICATORS</b>	
AC Mode	Green LED lighting
Battery Mode	Yellow LED flash
Fault	Red LED lighting
<b>PROTECTION</b>	
Full Protection	Short circuit, Overload , Overcharge and overdischarge protection
<b>ALARM</b>	
Battery Mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 second
Fault	Continuously sounding
<b>PHYSICAL</b>	
Approx , Dimension D X W X H (mm)	345 x 123 x 189
Approx. Net Weight (kg)	11.95
<b>OPERATING ENVIROMENT</b>	
Humidity	0-90 % RH @ 0- 40°C (non-condensing)
Noise Level	Less than 40dB
<b>MANAGEMENT</b>	
Communitacion port	For Choice (USB&RJ45)